
Wind Signs

Available in 3 Sizes

- Resists head-on winds up to 60 mph*
 *wind resistance varies for each size frame, see reverse side for details
- Change signs in seconds
 - "Quick-Change"™ feature, signs easily slide in and out
 - use Coroplast[™] signs or other material 3/16" thick or less
- All plastic frame
 - eliminates torn, bent, or rusted frames
- Plastic base has two built-in wheels
 - can be filled with dry sand
- Tool free assembly

signs 28" x 44"

Wind Sign II signs 24" x 36"



Coil springs resist strong winds and return the sign to an upright position





Patented slot design



"Stay Tabs″™ keep sign securely in place (On Wind Sign Deluxe and Wind Sign II)




Wind Sign signs 22" x 28"

Wind Signs Available in 3 Sizes

Specifications	Wind Sign	Wind Sign II	Wind Sign Deluxe™
Color	Gray	Gray	Gray
Dimensions (Frame Only)	32.75"H x 24"W x 2.5"D	42.9"H x 26"W x 2.5"D	51"H x 30"W x 2.5"D
Dimensions (Base Only)	4.5"H x 26"W x 18"D	7.1"H x 28.7"W x 18.1" D	7.1"H x 28.7"W x 18.1" D
Dimensions Assembled	40"H x 26"W	53"H x 28.7"W	61"H x 30"W
Total Weight Assembled	16 lbs.	25 lbs.	30 lbs.
Weight (Base Only)	4.3 lbs.	9 lbs.	9 lbs.
Base Sand Ballasting	Use a max. of 85 lbs. of dry sand	Use a max. of 115 lbs. of dry sand	Use a max. of 115 lbs. of dry sand
Sign Insert Size	22" x 28" (3/16" thick)	24" x 36" (3/16" thick)	28" x 44" (3/16" thick)
Sign Insert Weight Limit	Max. of 2.5 lbs. per side	Max. of 5 lbs. per side	Max. of 5 lbs. per side

Wind Sign Visual Area of Sign 28" 22" x 26 3/4"

Wind Sign II Visual Area of 36" Sign 24" x 35 1/8"



Sand Ballasting Instructions For Wind Sign Deluxe and Wind Sign II


Unscrew cap from fill hole and fill with up to 115 lbs. of dry sand to achieve desired wind resistance. Sand should be level inside of base to maintain optimum balance. Shake gently to level sand.


Wind Sign Deluxe™			
Pounds of	Head-on		
Ballast	Wind		
Dallast	Resistance		
70 lbs	40 mph		
100 lbs	45 mph		
115 lbs	50 mph		

	Wind Sign II			
	Dd f	Head-on		
	Pounds of Ballast	Wind		
		Resistance		
	70 lbs	40 mph		
	100 lbs	55 mph		
	115 lbs	60 mph		



Sign Insertion Instructions For Wind Sign II and Wind Sign Deluxe™:








Slide through, pulling sign in front of bottom slot until sign hits the base



3. Push sign up into



4. Slide sign down into bottom slot

MADE IN THE USA

US PATENT 7,337,569 Other Patents Pending

PLASTICADE



7700 Austin Avenue Skokie, IL 60077 phone (800) 772-0355 fax (847) 966-8074 www.plasticade.com

Slide in a Message Board...

Available for Wind Sign, Wind Sign II, and Wind Sign Deluxe™



or a Marker Board

Available for Wind Sign and Wind Sign II

